

Excellence in seaming
卓越的接缝



333-712/02

1243-712/02

Special machines for tacking and basting work
用于点缝及临缝工作的特殊机器



Features特征:

- Special machine for tacking and basting of jackets, over-coats, shoulder pads, etc. 用于点缝及临缝夹克, 外套, 垫肩等的专用机器
- Easy drawing of the thread when shifting the workpiece 在移动工件时, 能轻松拉动缝线
- Reliable sewing start after thread trimming due to the solenoid-controlled thread tension 通过电磁铁控制线张力, 在剪线后能可靠地起始缝纫
- One-stitch tacking because of pedal-controlled inching 通过踏板微动控制, 能单针定位
- Option: Reliable and sturdy thread trimmer (-900/51) 选项: 可靠坚固的剪线装置 (-900/51)
- Max. speed: 1,000 s.p.m. 最高速度1000转/分钟

333-712:

锁缝线迹, 自动润滑

- Cylindrical material guide for good handling for bulky materials (e.g. shoulder on the jacket) 圆柱形材料导向可以很好地处理大件物料 (例如夹克上的肩部)
- Simple processing of materials up to a thickness of 18.0 mm, depending on the used needle system 根据使用的机针类型, 可以轻松加工厚度达18.0 mm的材料
- Detachable work plate (91-142058-71/895) for an easy conversion from cylinder-bed to flat-bed (Option) 可拆卸的工作板 (91-142058-71 / 895), 便于从圆筒臂转换到平板 (选配件)



1243-712:

锁缝线迹, 自动润滑

- For work on flat-lying parts, such as tacking work on jacket front edges 用于平放缝纫件的工作, 例如在夹克前缘上进行定位工作
- Simple processing of materials up to a thickness of 12.0 mm, depending on the used needle system 根据使用的机针类型, 可以轻松加工厚度达12.0 mm的材料

Versions版本:



PFAFF 333-712/02-6/01 BS
PFAFF 333-712/02-6/01-900/51
AS with thread trimmer and servo motor
带剪线装置和伺服电机



PFAFF 1243-712/02-6/01-900/56
BS with thread trimmer 带剪线装置